



EAM9202-06



EAM9202-03

- Ideal for the regulating experiment of extraction, back flowing, and distillation
- Independent and separate control function
- Max. temperature: 450°C
- Ceramic fiber with strong thermal resistance
- Stainless steel top cover with corrosion-proof

### Features

- ▶ Space saving design of the extraction mantle
- ▶ Ideal for the experiment processes for repeated extraction, back flowing, distillation for the fields of foods, fiber, surroundings, petroleum, chemicals
- ▶ Independent and separate temperature control at each different condition
- ▶ Heating temperature is controlled by the electronic energy regulator
- ▶ "Power On" and "Heater On" indicating lamp
- ▶ Inner mantle part of the heating element consists of soft glass fiber, protected from damage of the flask and excellent

contact between the heating element and flask and heating effectiveness is excellent

- ▶ Ceramic fiber with strong thermal-resistance has excellent thermal insulation and double housing design maintains low temperature of the mantle surface for user's safety
- ▶ With thermal resistance and durability bearing at the inner temperature over 450°C, strong metal housing and powder coating with corrosion-proof
- ※ Glassware is not included.

### General Specifications

- ▶ Heating Element Temperature : Up to 450°C max.
- ▶ Temp. Controller : Electronic energy regulator
- ▶ Temp. Display : Scale
- ▶ Thermal Insulation : Ceramic fiber
- ▶ Material : Powder coated metal case

- ▶ Top Surface : Stainless steel
- ▶ Support Rods : Ø 12,7mm dia.(standard)
- ▶ Indicator Lamps : Green-"Power on", Yellow-"Heater on"
- ▶ Power Supply : 220V or 110V 50/60 Hz

Model	Capacity	Watts	Number of positions	Dimensions WxDxH(mm)	Internal (height : mm)	Weight (Kg)	Price
EAM 9201-03	100ml	80W×3	3	450×240×80	45	4,6	
EAM 9202-03	250ml	150W×3	3	520×260×95	60	5,8	
EAM 9203-03	500ml	260W×3	3	580×280×105	75	6,7	
EAM 9204-03	1000ml	380W×3	3	670×310×115	85	7,9	
EAM 9201-06	100ml	80W×6	6	950×240×80	45	9,2	
EAM 9202-06	250ml	150W×6	6	1040×260×95	60	11,6	
EAM 9203-06	500ml	260W×6	6	1150×280×105	75	13,5	
EAM 9204-06	1000ml	380W×6	6	1340×310×115	85	15,8	